



## Specifications Philips LED Panel Recessed TrueLine RC515B Aluminum 24W 3400lm - 840 Cool White

[View Product](#)

### General Information

|                          |                             |
|--------------------------|-----------------------------|
| SKU                      | 225834                      |
| EAN                      | 8718696875353               |
| Brand                    | Philips                     |
| Manufacturer Name        | RC515B LED34S/840 PSU BCV W |
| Any Lamp all-in warranty | 5 Years                     |
| Average Lifetime (h)     | 70000                       |
| Series                   | Panel Led                   |

### Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 1x80            |
| Wattage                     | 24              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 3400            |

|                          |                               |
|--------------------------|-------------------------------|
| Luminous Efficacy (lm/W) | 141.7                         |
| IP-rating                | IP20                          |
| Impact Protection (IK)   | IK02 - 0.20 joule             |
| Fixture Connection       | PI [Push-in connector 3-pole] |
| Driver Included          | Yes                           |
| Power factor             | >0.90                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Operating Temperature | +10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | Aluminium                      |
| Housing               | Steel                          |
| Colour of material    | Aluminium                      |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 175x15cm |
| Length (mm)    | 1750     |
| Width (mm)     | 150      |
| Height (mm)    | 94       |

[Sensor Information](#) [Discover the largest lighting specialist in Europe](#) [Customised quotation](#)

Type of sensor



Up to 7 years warranty

No Sensor

⤵ Easy return process