



**Specifications Philips LED Panel**  
**CoreLine RC136B 25/34W 3100-4300lm**  
 - 840 Cool White | 60x60cm - UGR <19  
 - Dali Dimmable - Selectable Wattage - W5

[View Product](#)

## General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 241098                                  |
| EAN                      | 8719514512290                           |
| Brand                    | Philips                                 |
| Manufacturer Name        | RC136B 31S_37S_43S/840 PSD W60L60 OC W5 |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 50000                                   |
| Series                   | RC136B                                  |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 34                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 4300               |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 140               |
| IP-rating                | IP20/IP44         |
| Impact Protection (IK)   | IK03 - 0.35 joule |
| Fixture Connection       | Cable, 5-pole     |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| EOC8                  | 51229000                       |
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 597     |
| Width (mm)     | 597     |
| Height (mm)    | 44      |

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|